

IKONOS-based Simulations of Landsat 7 VNIR Data: Comparison with Actual, Coincident Images

Slawomir Blonski

Lockheed Martin Space Operations
Commercial Remote Sensing Program
NASA Stennis Space Center

March 19 - 21, 2001

phone: (228) 688-1944

e-mail: sblonski@ssc.nasa.gov



Contributors

Stennis Space Center

Robert Ryan LMSO, Stennis Mary Pagnutti LMSO, Stennis Charles Smith LMSO, Stennis


Vicki Zanoni NASA, Stennis Tom Stanley NASA, Stennis

Robert Schowengerdt Stephen Schiller Univ. of Arizona
South Dakota State Univ.










IKONOS V&V: Landsat 7 Simulations

- IKONOS images were used to simulate four VNIR bands of Landsat 7 level 1G images (similar processing level: radiometric correction, georeferenced with cubic-convolution resampling, UTM projection)
- In year 2000, 92% of Landsat 7 images distributed by USGS EROS Data Center were on the level 1G
- Simulations validated by comparing results with actual coincident Landsat 7 images
- Results provide insights on radiometric calibration, spatial resolution, and geolocation accuracy of the image products




December 14, 2000 Distance of 35 km




Simulation Algorithm: PSF Synthesis

Stennis Space Center



For each spectral band, the Landsat 7 image (*I'*) is simulated by linear combination of the IKONOS image (*I*) pixels:

$$I'_{kl} = rac{c_{ijkl}I_{ij}}{c_{ijkl}}$$



The coefficients c_{ijkl} are found independently for each Landsat 7 pixel by solving (in the least squares sense) for a given set of points (x, y) the following equation which expresses an effective point spread function (PSF') of the Landsat 7 image as a linear combination of the IKONOS image PSF's:

$$PSF'(x-x_{l}, y-y_{k}) = c_{ijkl}PSF(x-x_{j}, y-y_{i})$$



Comparison of Spectral Response






Image Overlap: Brookings, SD

Stennis Space Center


Images acquired on June 30, 2000


IKONOS

po_41229 17:12 UTC 4 m GSD

Landsat 7

p29r29 17:03 UTC 30 m GSD





Both image products in map orientation (north up)

Geolocation difference

Band 1: 113 m [-11.25, -112.50] Band 2: 109 m [-11.25, -108.75] Band 3: 109 m [-11.25, -108.75] Band 4: 109 m [-7.50, -108.75]




Image Comparison: South Dakota



Actual Landsat 7 image



Simulated Landsat 7 image



Image Detail Comparison



IKONOS image



Simulated Landsat 7 image




Actual Landsat 7 image




Stennis Space Center

Based on updated IKONOS radiometric calibration coefficients:

 $L = DN / 630 \text{ sr} \cdot \text{cm}^2 \cdot \text{mW}^{-1}$






- Dispersion of points on the scatter plot due to noise and geolocation differences
- Presence of saturated Landsat 7 pixels
- Nonlinear response of Landsat 7 at higher radiance most likely due to saturation of the original L7 pixels (before resampling to L1G)




Stennis Space Center

Based on updated IKONOS radiometric calibration coefficients:

L = DN / 650 sr·cm²·mW⁻¹






- Dispersion of points on the scatter plot due to noise and geolocation differences
- Presence of saturated Landsat 7 pixels
- Nonlinear response of Landsat 7 at higher radiance most likely due to saturation of the original L7 pixels (before resampling to L1G)




Stennis Space Center


Based on updated IKONOS radiometric calibration coefficients:

 $L = DN / 840 \text{ sr} \cdot \text{cm}^2 \cdot \text{mW}^{-1}$






- Dispersion of points on the scatter plot due to noise and geolocation differences
- Presence of saturated Landsat 7 pixels
- Nonlinear response of Landsat 7 at higher radiance most likely due to saturation of the original L7 pixels (before resampling to L1G)




Stennis Space Center

Based on updated IKONOS radiometric calibration coefficients:

 $L = DN / 750 \text{ sr} \cdot \text{cm}^2 \cdot \text{mW}^{-1}$






- Dispersion of points on the scatter plot due to noise and geolocation differences
- Nonlinear response of Landsat 7 at higher radiance most likely due to saturation of the original L7 pixels (before resampling to L1G)



Sensitivity to Radiometric Calibration

Stennis Space Center

Use of initial IKONOS radiometric calibration coefficients result in distorted scatter plots for bands 2, 3, and 4






Different Image Orientation

Stennis Space Center

The simulations were also conducted for images with different orientation:

- IKONOS
 po_41229 17:12 UTC
 4 m GSD
 map (north up) orientation
- Landsat 7
 p29r29 17:03 UTC
 28.5 m GSD
 nominal (satellite)
 orientation



Geolocation difference

Band 1: 168 m [-14.66, -167.40] Band 2: 168 m [-14.66, -167.40] Band 3: 168 m [-14.66, -167.40] Band 4: 168 m [-14.66, -167.40] Geolocation difference is still within the limits given by the geometric accuracy of Landsat 7 level 1G and IKONOS standard original image products (250 m)



Image Comparison: Different Orientation



Actual Landsat 7 image


Simulated Landsat 7 image



Radiometric Comparison: Orientation

Stennis Space Center

For the case when the input IKONOS image has a different orientation than the output Landsat 7 image, the scatter plots are more dispersed than in the case of images with the same orientation





Effect of Spatial Resolution






Image Comparison: MTFC On / Off



Simulated Landsat 7 image created from the IKONOS image processed with the MTF compensation



Simulated Landsat 7 image created from the IKONOS image processed without the MTF compensation



Radiometric Comparison: MTFC On / Off

Stennis Space Center

Band 4






Image Overlap: Florida

Stennis Space Center

Images acquired on September 7, 2000


• IKONOS

po 45306 15:56 UTC 4 m GSD

• Landsat 7

p16r43 15:47 UTC 30 m GSD





Both image products in map (north up) orientation

Geolocation difference

Band 1: 0 m

Band 2: 0 m

Band 3: 0 m

Band 4: 0 m





Image Comparison: Florida



Actual Landsat 7 image



Simulated Landsat 7 image



Radiometric Comparison: Florida

Stennis Space Center

Orthogonal streaks are due to development and movement of clouds during the time between acquisitions of the two images






Image Overlap: Oklahoma

Stennis Space Center


Images acquired on May 22, 2000


IKONOS

po 37741 16:52 UTC 4 m GSD

• Landsat 7

p28r35 16:59 UTC 30 m GSD





Both image products in map (north up) orientation

Geolocation difference

Band 1: 0 m Band 2: 0 m Band 3: 0 m Band 4: 0 m





Image Comparison: Oklahoma



Actual Landsat 7 image



Simulated Landsat 7 image



Radiometric Comparison: Oklahoma

Stennis Space Center

Difference in atmospheric conditions (high cirrus clouds) resulted in attenuation of Landsat 7 at-sensor radiance and increased scattering






Image Overlap: Oregon

Stennis Space Center


Images acquired on August 8, 2000


IKONOS

po 45281 19:13 UTC 4 m GSD

• Landsat 7

p46r29 18:47 UTC 30 m GSD





Both image products in map (north up) orientation

Geolocation difference

Band 1: 47 m [45.00, -15.00] Band 2: 51 m [48.75, -15.00] Band 3: 47 m [45.00, -15.00] Band 4: 47 m [45.00, -15.00]



Image Comparison: Oregon



Actual Landsat 7 image




Simulated Landsat 7 image



Radiometric Comparison: Oregon

Stennis Space Center

Local differences in pixel geolocation create characteristic dispersion in the scatter plots





Final Remarks

- IKONOS images can be accurately transformed to mimic VNIR image data created by Landsat 7
- Mitigation of effects created by differences in acquisition time (solar angle), collection geometry (azimuth and elevation angle), and spectral response may be needed to achieve the accurate results
- The simulations become less accurate when atmospheric conditions are different (clouds) or when terrain relief creates local geolocation differences